

1 ud/caja



Description

Multi-purpose stool for offices and public spaces.

Components

Shell:

- Polypropylene + glass fibre.
- Manufactured by injection moulding.

Metal structure:


- Ø20x2 mm steel tube. Epoxy paint with 50µm thickness..
- Footrest: Ø11 mm drawn rod. Epoxy paint with 50µm thickness.

Main Features

- Robust.
- Antistatic.
- Mobile.
- Easy to clean.
- Silent.
- Ergonomic shell.
- Stain-resistant.
- Optional solid (non-perforated) backrest.
- Backrest opening for better ventilation.
- Optional seat panel for upholstery.
- Designed according to UNI EN 10130 standard.

Details and Options

Perforated
backrest



Non-Perforated
backrest



Optional

Upholstered



Optional

Structure



Finishes

Shell



Anthracite



Cement Grey



Cane Green



Sand



Coral Red

Structure



Black

Maintenance

- Check the condition of the metal structure.
- Check the condition of the shell.
- Ensure there are no cracks or dangerous breaks.
- Check the condition of the end caps.

Cleaning

- Cleaning of the metal structure: methylated spirits may be used only in extreme cases. Never use solvent.
- Remove dust with a dry cloth or brush. Clean with a sponge or cloth using neutral soap or a mixture of water and vinegar. For embedded dirt, grease residues or stains, ammonia can be used.